RETAIL WEIGHING SOLUTION[™]

PR-II series

Price Computing Scale

As an electronic price-indicating scale with a maximum of 1/30,000 resolution, PR-II is designed in a low profile to be conveniently used in open market such as butcher's shop and groceries.



Low Profile Design

Up to 7 Direct PLUs Memory Function

A RULLE

LCD Display & Back light (White)



PR-II

Low Profile Design Existing Products



Μ4



Scan with your smartphone to find more products

Pole Type





PR-II series


Price Computing Scale



SPECIFICATIONS

MODEL	PR2-03	PR2-06	PR2-15	PR2-30
Capacity	3kg	6kg	15kg	30kg
е	0.5/0.2/0.1(g) 1/0.5g(certificate)	1/0.5/0.2(g) 1/0.5g(certificate)	2/1/0.5(g) 5/2g(certificate)	5/2/1(g) 10/5g(certificate)
Resolation	1/3,000 ~ 1/30,000	1/3,000 ~ 1/30,000	1/3,000 ~ 1/30,000	1/3,000 ~ 1/30,000
Display	6/6/6 Digit LCD & Back light (White) Minimuam			
Symbols	STABLE, ZERO, TARE, Battery Remaining battery life indicated HI / OK / LO & Lb & 100g & Oz & ADD & PAY(Triangular symbol indicated)			
Keys	NUMBER , ZERO, TARE, FUNCTION , M1 ~ M7 KEY			
Functions	Direct PLU 7, Unit Conversion, Power Sleep Mode, Backlight Mode, Price Summation and Pay Function			
Operation Time	Apporx. D size Battery = 500hr Or Pb Battery = 400hr (Backlight off)			
	Approximately 900 hours consecutively when equipped with Mn Battery and Pb Battery together			
Option	RS-232 (Print , Command), Pole Type , Mn Battery, USB Port			
Power	1.5V x 3 units (D size Battery) or Pb battery 4V 4Ah or 6V Adapter			
Dimensions	330 (W) x 380(D) x 105(H)			
Platter Size	330 (W) x 235(D)			

DIMENSION



💮 ТОУ 🚯 (Е 🔍

FEATURE

- High Resolution for Weighing (Max. 1/30,000)
 - A maximum of 900 hours of battery life when used with Mn and Pb batteries together
- Low Profile Design
- Excellent applicability in open market with a low body
- Hi / OK / Low Limit Function
- USB Port for COMM. & Power (Option)



- Price Summation & Pay Function
- Up to 7 Direct PLUs Memory Function



LCD Display & Back light (White)



· Rear Display for Customer (Bench type)

OPTION

- RS-232 (Print, Command)
- Pole Type
- Mn Battery
- USB Port





http://www.globalcas.com