## MP SERIES

# Cost effective solution to weigh on the go!

MP Pallet scale raises efficiency for your work, simplifies logistic processes, and saves time and space. It is the ideal solution for fast and precise mobile weighing in industrial and warehousing applications.







High-visibility display

Easy to access the battery pack

Solid & optimum design for industrial application



gh-visibility display

Easy to access the battery pac

Solid & optimum design for industrial application

### MP series Pallet Scale



#### Verified pallet truck scale (with OIML & EC type approval)

MP has a OIML & EC type approval for a mobile device.

#### **High-Visibility display**

You can easily see the weight value in any distance via clear LED and LCD display



#### Easy to access the battery pack

Easily accessible to the recharegeable battery pack for charging & installing.



#### **Features**

- Verified pallet truck scale(With OIML & EC type approval)
- Easy to access the battery pack
- · High-visibility display
- 10 numeric keys & 5 function keys
- · Hydraulic lift and low
- Durable polyurethane wheels
- · Solid and optimum design for logistics
- . Built-in thermal printer (optional)

#### **Options**

- Thermal printer
- Wheel brake

#### **Application**

- Materials handling
- Warehousing
- Industrial applications

#### Specification

| Model                  |      | MP-1  |     |     | MP-1.5 |     |     | MP-2 |     |     |
|------------------------|------|---|-----|-----|--------|-----|-----|------|-----|-----|
| Product size           | TYPE | А   | В   | С   | Α      | В   | С   | Α    | В   | С   |
|                        | W    | 540   | 620 | 705 | 540    | 620 | 705 | 540  | 620 | 705 |
|                        | L    | 1140  |     |     | 1140   |     |     | 1140 |     |     |
| Capacity (kg)          |      | 1000  |     |     | 1500   |     |     | 2000 |     |     |
| Readability (kg)       |      | 0.5   |     |     | 0.5    |     |     | 1    |     |     |
| Display                |      | 6 digit LED(Height: 25mm), 5 digit + sign LCD(Height: 24mm) |     |     |        |     |     |      |     |     |
| Power                  |      | 6VDC / 10Ah rechargeable battery) (6VDC / 2Ah charger)      |     |     |        |     |     |      |     |     |
| Battery operating time |      | 85 Hours  |     |     |        |     |     |      |     |     |
| Battery charging time  |      | 10 Hours  |     |     |        |     |     |      |     |     |
| Operating temperature  |      | -10°C ~ +40°C   |     |     |        |     |     |      |     |     |
| Option                 |      | Thermal printer, Wheel brake                                |     |     |        |     |     |      |     |     |

#### **Dimensions**

















