LABORATORY WEIGHING SOLUTION[™]

XEPLUS series

Micro-weighing Scale

XE PLUS is a micro-weighing scale with excellent weighing performance with 1/30,000 resolution. It can measure from 300 g to 6,000 g, and be used for direct sales to the public without auxiliary indicating device, extended indicating device according to OIML R76:2006. The operating temperature is from 5 to 40 °C. So, it can be used in any industrial field. XE PLUS will open a new prospect in micro-weighing scale with high performance, various interfaces, and ease of charge.

- Excellent performance (Load cell protection device, Kensington lock, Wind Shield)
- Various interface (Axillary display, IM-WORKS, Various printer connectable)
- Easy to charge (Rechargeable battery, Dry battery selectable)

Ð



Scan with your smartphone to find more products





XE PLUS series

Micro-weighing Scale



- Excellent weighing performance with 1/30,000 resolution
- Direct sales to the public with same e, d
- Satisfaction with OIML R76:2006 standard
- Various functions
- (Load cell protection device, Kensington lock, Wind Shield) • Various interfaces
- (Axillary display, IM-WORKS, Various printer connectable) • Rechargeable battery
- Compact design
- IR sensor (touchless key)



TOUCHLESS KEY

Applied the IR Sensor, the XE can zero, tare and print only with hand gestures.



Load cell protection device

Fine products require precise protection. XE is holding the loadcell protection locker for safe transportation. You do not have to worry about breakage.



Various interfaces

Remote display, printers (Dot,Ticket, label) and the IM-WORKS can be connected at the same time.



CAS BLDG., 1315, YANGJAE-DAERO, GANGDONG-GU, SEOUL, KOREA TEL _ 82 2 2225 3500 FAX _ 82 2 475 4668 Specifications are subject to change without notice improvement


Specification

Model	XE PLUS			
Max(g)	300	600	1500	3000
e=d (g)	0.01	0.02	0.05	0.1
Resolution	1/30,000 (Single interval)			
Display	6 digit LCD (with Backlight)			
Кеу	7 EA (Power, Model, Unit, Zero, Tare, Average, Print)			
Operation temperature	5~40°C			
Power	DC 12 V Adaptor			
Platter Size (mm)	300, 600: Ø128mm 1500, 3000, 6000: 155 X 143mm			
Product Size (mm)	272 (W) x 180 (L) x 74 (H)			
Product Weight (kg)	Approx. 1.39			

Options

- Dry battery, Rechargeable battery (AA Size x 4 EA)
- CD-300 Auxiliary Display
- USB Cable (B type, PC communication)
- RS-232C Cable (Printer, PC Communication)

Dimensions





www.globalcas.com